

CCHH3200



32" Sunlight Readable LCD Display



Specifications

Lcd Panel	
Brightness	600 cd/m ²
Contrast Ratio	1500:1
Viewing Angle	H:176°/V:176°
Response Time	6.5ms (GTG)
Supported colors	16.7M colors
Resolution	1366x768(16:9)
Display Features	
Horizontal Frequency	30 - 65 KHz
Vertical Frequency	56 ~ 75 Hz
Input Resolution	1366 x 768 @60Hz (Analog) 1366 x 768 @60Hz (Digital)
DDC	DDC2B
OSD Control	RS232C, Push button, IR Remote Controller
OSD Language	English, Japanese, Chinese
Physical Features	
Connector	15pinD-Sub/DVI/ Component / S-video / AV
Dimensions with Stand	793 x 511.7 x 180 mm (WxHxD)
Weight with Stand	16kg
Wall / Arm Mount Type	200mm x 200mm VESA

Special Features	
Multimedia	PIP, PAP, Zoom
Fanless Design	Yes
Source Auto Detect	Yes
Communication Port	D-Sub 9 Pin, RJ45 In/Out
(Transport Protocol)	(RS-232, RS-485 In/Out)
Power Consumption	
Power Supply	AC 100V-240V (50/60 Hz)
Normal Operation	165W
Suspend / Standby	15W
Power Off Mode	15W
Environmental	
Operating Temperature	5°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	85%RH
Storage Humidity	85%RH
Options	
Protective Surface	4mm Tempered Glass (AG/AR)

Dimensions

