

IP66 Full Completely Sealed Stainless Steel Cabinet

32" LCD Chassis mount monitor, 1366x768, VGA,
without speaker High brightness 1000 nits,
Optical bonding with 5mm protected glass

(Model: ECHW3200HBIP)

Features:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 32" viewable diagonal area	
	Active Area / Pixel Pitch	697.69(H) x 392.26(V) mm / 0.51(H) x 0.51(V) mm	
	Native Resolution / Colors	1366(H) x 768(V) / 16.7 Million	
	Brignthess / Contrast	1000 cd/m ² (typ) / 2000 : 1	
	Response Time	< 6 ms (G-to-G)	
	Viewing Angle (typical)	H. 178o (- 89o ~ + 89o) , V. 178o(- 89o ~ + 89o)	
	Light Source	CCFL light source , Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F _h : 30 - 82Khz , F _v : 50 -75Hz
	Audio System	3W Amplifer x 2, without speaker	
Input Terminals	1 x VGA(15 Pin Female D-Sub), 1 x DC Power Connector		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA 200 x 100 mm)		
	IP66 rating water resistance, Optical Bonding with 5mm Anti-vandal protected glass		
Power	24VDC input (External power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz)		
Power Consumption	Operation / Power Saving	95 watt , < 2 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	With Flanges(W x H x D) : TBD	
		Without Flanges(W x H x D) : TBD	
	Carton	W x H x D = TBD	
Weight	N.W. / G.W.	20.0 Kgs / 22.0 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)	
Options	Video / TV	Enhanced Panel	Others
	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	SV + AV + AV_Looping	High brightness panel	Motion Sensor
	SV + AV + TV	Wide Temperature	Light Ssensor
		Transflective 550 nits	Auto-Dimming

Mechanical Drawings:

